

Horse HM-1.4TT

Unidirectional Carbon Fiber Laminate For Strengthening

Description HM-1.4TT is a high strength, high modulus unidirectional carbon fiber reinforce polymer(CFRP) for structural strengthening. It is bonded onto the structure as external reinforcement using HM-120CP epoxy resin as the

Application Range

- **Load Increase**
 - Increased live loads in warehouses
 - Increased traffic volumes on bridges
 - Installation of heavy machinery in industrial buildings
 - Vibrating structures
 - Changes of building utilization
- **Seismic Reinforcement**
 - Concrete column wrapping, beam strengthening, wall strengthening, slab strengthening
 - Masonry walls reinforcement
- **Damage to Structural Parts**
 - Aging of construction materials
 - Fire
 - Vehicle impact
- **Change of Structural System**
 - Removal of walls or columns
 - Removal of slab sections for openings
- **Design or Construction Defects**
 - Lack of reinforcing bars
 - Lack of member cross section
- **Improve Structural State**
 - Reduce the deformation
 - Reduce the stress of the original structure
 - The crack reinforcement

- Product Characteristic**
- High strength, high toughness, high modulus
 - Soft and flexible, light self weight, easy to install
 - Long shelf life and aging resistance
 - High temperature resistance
 - Acid, alkali & salt resistance
 - Seismic resistance
 - Environmental-friendly
 - Can be used for shear strengthening, confinement strengthening, flexural strengthening
-

Horse Advantage

■ **Aviation Grade Yarn**

Japan imported aviation grade raw material, excellent quality and stable performance.

■ **World Leading Production Line**

Germany imported intelligent production line. Point to point active weft insertion. No damage to the yarn during the weaving process.

excellent flatness enable epoxy easy to penetrate, hence high bonding strength can be achieved

■ **Patented Tension Controlling System**

Our own developed whole process tension controlling system. It ensures the constant tension, low dispersion.

■ **Large output and Timely Delivery**

5 million square meters annual output. 100 thousand square meters regular daily stock.

Package

This product is rolled into a ring and uses a belt to bind. The length of the laminate is 100m, the width is 50mm and 100mm, the thickness is 1.2mm and 1.4mm.

Basic Information

Model	HM-1.4TT
Appearance	Black laminate
Length	100m
Width	Regular width is 50mm, 100mm, other width can be customized.
Shelf Life	50 years
Storage Conditions	Store in dry conditions at 40°F to 95°F (4°C to 35°C)
Braiding	0° (Unidirectional)

Performance indexes

Tensile Strength	
Mean Value	3300 MPa
Design Value	2900 MPa
Tensile Elastic Modulus	
Mean Value	210,000 MPa
Design Value	190,000 MPa
Interlaminar Shear Strength	50 MPa
FRP With Base Materials Bonding Strength(MPa)	For concrete and masonry: ≥ 2.5 Mpa, concrete cohesion damage
Elongation	1.70%
Thickness	1.4mm
Temperature Resistance	$> 300^{\circ}\text{F}$ ($> 150^{\circ}\text{C}$)
Fiber volume content	$\geq 65\%$
Density	0.058 lbs./in ³ (1.6g/cm ³)

Construction Process

1. Setting out according to designing;
 2. Polish the surface of concrete surface to remove painting of the surface, blow out the floating dust with compressed air;
 3. Prepare ingredients: agitate component A and B evenly in packaging bucket by weighting in accordance with the weight ratio A: B =2:1;
 4. Installing: Past the above mixed glue compounds onto the surface of carbon fiber plate evenly, please avoid bubbles;
 5. Anchorage: paste the carbon fiber plate onto the concrete surface and fixed with steel strip, remove excessive glue compounds around, and fix With Steel framework;
 6. Maintenance: conservation time should be no less than 24 hours at room temperature.
-

Points for Attention

The construction workers should take necessary protective measures such as wearing masks, gloves, goggles etc. Pay attention to fire prevention and maintain good ventilation on site.

Carbon fiber material is conductive, be careful to the electrical equipments around.

For more information, please visit our website at www.horseen.com



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE